

CW CAR WASH



SPECIAL SERIES



The highest tecnology in Car Wash

For car wash and industrial applications up to 60°C (140°F)
 Pour car wash et applications industrielles jusqu'à 60°C (140°F)
 Für car wash und industrielle Einsätze bis 60°C (140°F)
 Para car wash y aplicaciones industriales hasta 60°C (140°F)
 Per car wash e applicazioni industriali fino a 60°C (140°F)

Up to 60°C (140°F)

PUMPS LISTED ACCORDING TO FLOW RATE
 TABELLE POMPES ORDONNÉES SUIVANT LE DÉBIT
 PUMPENTABELLE NACH FÖRDERLEISTUNG ANGEORDNET
 TABLA DE BOMBAS EN ORDEN DE CAUDAL
 TABELLA POMPE IN ORDINE DI PORTATA

Flow rate Débit Förderleistung Caudal Portata		r.p.m. tr./min u.p.m. r/min	Pressure Pression Druck Presión Pressione			MOD.	Pag.
l/min	G.P.M. (U.S.A.)		bar	Mpa	p.s.i.		
11	2.91	1450	200	20	2900	C2W2011	54
12	3.17	1450	200	20	2900	C2W2012	54
13	3.43	1450	200	20	2900	C2W2013	54
13	3.43	1450	200	20	2900	C3W2013	55
15	3.96	1450	200	20	2900	C3W2015	55
21	5.55	1450	200	20	2900	C3W2021	55

Up to 85°C (185°F)

PUMPS LISTED ACCORDING TO FLOW RATE
 TABELLE POMPES ORDONNÉES SUIVANT LE DÉBIT
 PUMPENTABELLE NACH FÖRDERLEISTUNG ANGEORDNET
 TABLA DE BOMBAS EN ORDEN DE CAUDAL
 TABELLA POMPE IN ORDINE DI PORTATA

Flow rate Débit Förderleistung Caudal Portata		r.p.m. tr./min u.p.m. r/min	Pressure Pression Druck Presión Pressione			MOD.	Pag.
l/min	G.P.M. (U.S.A.)		bar	Mpa	p.s.i.		
13	3.43	1450	200	20	2900	C3W2013HT	55
15	3.96	1450	200	20	2900	C3W2015HT	55
21	5.55	1450	200	20	2900	C3W2021HT	55





C2W series

For car wash and industrial applications up to 60°C (140°F)
 Pour car wash et applications industrielles jusqu'à 60°C (140°F)
 Für car wash und industrielle Einsätze bis 60°C (140°F)
 Para car wash y aplicaciones industriales hasta 60°C (140°F)
 Per car wash e applicazioni industriali fino a 60°C (140°F)



Pump type Type de pompe Pumpentype Tipo de bomba Tipo di pompa	Flow rate Débit Förderleistung Caudal Portata l/min GPM (U.S.A.)		Max.pressure Pression Druck Presión Pressione bar MPa p.s.i.			r.p.m. tr./min u.p.m. r/min g./min	Power Puissance Leistung Potencia Potenza kW hp		Weight Poids Gewicht Peso Peso kg	Inlet Entrée Eingang Entrada Entrata	Outlet Sortie Ausgang Salida Uscita	Dimensions Dimensions Dimension Dimensiones Dimensioni mm
C2W2011	13	3.43	200	20	2900	1750	5,00	6,8	7	G1/2 F	G3/8 F	242x215x122
	11	2.91	200	20	2900	1450	4,19	5,7		G1/2 F	G3/8 F	
C2W2012	14	3.70	200	20	2900	1750	5,37	7,3		G1/2 F	G3/8 F	
	12	3.17	200	20	2900	1450	4,55	6,2		G1/2 F	G3/8 F	
C2W2013	15	3.96	200	20	2900	1750	5,74	7,8		G1/2 F	G3/8 F	
	13	3.43	200	20	2900	1450	5,00	6,8		G1/2 F	G3/8 F	